



SIM CARD INSTALLATION

Model	CTM-ONE
Revision	Rev B

Revision Control

Description	Revision	Date
Initial version	Rev A	2018-01-04
Reformatted version	Rev B	2021-09-07

Table of Contents

- Revision Control..... 1
- Table of Contents2
- Before You Begin..... 3
- Inserting a SIM Card Step by Step 3
 - 2.1 Step 1 - Remove Cover 3
 - 2.2 Step 2 - Insert SIM Card(s)..... 4
 - 2.3 Step 3 - Reassemble Cover 5

Before You Begin



A 3/32" Allen key (supplied) is required to remove the 4 screws holding the cover in place.

IMPORTANT: MAKE SURE TO PROTECT THE DEVICE AGAINST STATIC DISCHARGE. ENSURE YOU ARE ADEQUATELY GROUNDED TO PREVENT DAMAGE TO THE DEVICE

Inserting a SIM Card Step by Step

2.1 Step 1 - Remove Cover



To gain access to the dual-SIM card holder, remove the 4 socket head cap screws using a 3/32" Allen key (supplied).

After completely loosening the 4 screws lift off the cover. You may have to wiggle the cover to completely disengage it from the chassis.

2.2 Step 2 - Insert SIM Card(s)



For single SIM card installation, insert the SIM card into the upper slot of the dual-SIM holder. Ensure that the copper contacts are facing downward (chamfered corner to the front right).



If applicable, the second SIM card can be inserted into the lower slot of the dual-SIM holder.

2.3 Step 3 - Reassemble Cover



Ensure that the gasket is in place when the Battery cover is reinstalled.



Tighten screws in a crisscross pattern until snug for optimal weather tight seal.

You have now completed the SIM card(s) installation.